

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : HYFLEX SATIN FLOOR SEAL
 Product code : CS91
 UFI Number : 4H5Q-00YG-400E-MMW5
 Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
 Industrial/Professional use spec : For professional use only
 Use of the substance/mixture : Designed for use on stone, concrete, terrazzo, porous linolium, thermoplastic and wood floors.
 Produces a low gloss finish which is tough and durable.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Bio-Productions
 72 Victoria Road
 Burgess Hill - United Kingdom
 T 0044 (0) 1444 244000 - F 0044 (0) 1444 244999
technical@bio-productions.com - www.bio-productions.com

1.4. Emergency telephone number

Emergency number : 0044 (0) 1444 244000 (office hours only)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital, Guy's & St Thomas' Hospital Trust	Dudley Road B18 7QH Birmingham	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request
 EUH208 - Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazolin-3-one(2634-33-5). May produce an allergic reaction
 Precautionary statements (CLP) : P102 - Keep out of reach of children
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P301+P312 - IF SWALLOWED: Call a doctor, a POISON CENTER if you feel unwell

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
POLYTHENE WAX EMULSION		3 - 5	Eye Irrit. 2, H319
3-butoxypropan-2-ol, propylene glycol monobutyl ether	(CAS No) 5131-66-8 (EC no) 225-878-4 (EC index no) 603-052-00-8 (REACH-no) 01-2119475527-28	1 - 3	Eye Irrit. 2, H319
(2-methoxymethylethoxy)propanol [DPGME] substance with a Community workplace exposure limit	(CAS No) 34590-94-8 (EC no) 252-104-2	1 - 3	Not classified
POLYPROPYLENE WAX EMULSION		1 - 3	Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First aid measures general : If you feel unwell, seek medical advice (show the label where possible)
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First aid advice Ingestion : Do not give anything by mouth to an unconscious person. Wash mouth out with water, then drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : The product is not flammable. Use extinguishing agent suitable for surrounding fire. Foam. Water spray. Dry powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)		
EU	IOELV TWA (ppm)	10 ppm
(2-methoxymethylethoxy)propanol [DPGME] (34590-94-8)		
EU	Local name	(2-Methoxymethylethoxy)-propanol
EU	IOELV TWA (mg/m ³)	308 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	Notes	Skin
United Kingdom	Local name	(2-methoxymethylethoxy) propanol
United Kingdom	WEL TWA (mg/m ³)	308 mg/m ³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: No data available
Odour threshold	: No data available
pH	: ≈ 8
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: ≈ 0
Boiling point	: > 100 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

Relative density	: No data available
Density	: ≈ 1.03
Solubility	: Soluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidising properties	: Oxidising solids Not applicable.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
LD50 oral rat	3300 mg/kg
LD50 dermal rat	> 2000
LC50 inhalation rat (Vapours - mg/l/4h)	> 3.5 mg/l/4h

Skin corrosion/irritation : Not classified
pH: ≈ 8

Serious eye damage/irritation : Not classified
pH: ≈ 8

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8)	
LC50 fish 1	> 560 mg/l
EC50 Daphnia 1	> 1000 mg/l

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

12.2. Persistence and degradability

HYFLEX SATIN FLOOR SEAL

Persistence and degradability

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

No additional information available

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
UN-No. (IMDG) : Not applicable
UN-No. (IATA) : Not applicable
UN-No. (ADN) : Not applicable
UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Changes from Previous version:

- UFI number added in section 1.1
- P-Statements added in Section 2.2

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rai
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:

Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H319	Causes serious eye irritation

HYFLEX SATIN FLOOR SEAL

Safety Data Sheet

according to Regulation (EU) 2015/830

EUH208	Contains . May produce an allergic reaction
EUH210	Safety data sheet available on request

SDS EU (Reach Annex II) GREEN

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product