

PERMASEAL FLOOR SEAL

Stone Floor Seal



Permaseal Stone Floor Seal is a colourless fluoropolymer that bonds and penetrates internal and external surfaces to provide a non-slip protection against water, oil, soiling and staining. It prevents the staining of stone, terracotta, concrete, terrazzo, marble, brick and other porous surfaces. Permaseal Stone Floor Seal provides superb abrasion and aging resistance to the substrate.

- Transparent, so will not affect the appearance (will not give the surface a shiny appearance)
- Protects surface from UV
- Allows surface to dry quickly
- For internal and external use
- Will not alter the slip hazard of the floor when wet or dry
- Protects against staining
- Suitable for external use on concrete and patio tiles



APPLICATION

Allow 30 minutes to an hour to allow the water to evaporate and the polymer to penetrate the surface. Avoid direct contact with the substance and the formation or spread of mists in the air.

DIRECTIONS

Easy to apply with a flat mop, brush, roller or low pressure garden sprayer. Make certain the area to be treated is clean and soil free before applying.

Permaseal coverage will depend on the porosity of the surface to be treated. Make certain the whole area is covered properly.

PACKAGING

Order Code : Y-CS1000

Pack Size: 2 x 5L

STORAGE

Store in original, sealed container.

Keep lid tightly closed when not in use

Keep out of the reach of children.

Protect from freezing